

## Assembly device mount

Universal gear tray installation for ballea-BAM/ THLA/1500-1, -2 made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-less attachment with snap-in catches and safety bar. Housing colour traffic white RAL 9016; . Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. With connection cable 1.2m for connecting luminaire and track. The safety bar to guarantee protection against ball impact is included in delivery. Order separately for luminaire attachment BW-SDT or SDLAD. IP20

## CHARACTERISTICS

Order number	18015303100
EAN number	4020863497805
Commodity code	94059900
Certification mark	IP 20, Protection class I, Indoor, CE

## ELECTRICAL ENGINEERING

Mains voltage	230V/50Hz
---------------	-----------

## MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	314mm x 55mm x 45mm
Weight (net)	0.4kg
Type of installation	Mounting rail system installation, Ceiling-mounted mounting rail installation, Ceiling-mounted mounting rail installation on T-system, Pendulum mounting rail assembly on chain, Pendulum mounting rail installation on steel cable

## Dimensions

L	314 mm	Length
B	55 mm	Width
H	45 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/18015303100>

