

netlife light management function module device mount IP 54

Blank cover IP54 made of galvanised, profiled sheet steel with zinc coating and combined with polyester resin paint guarantees good corrosion protection; with two rotary catches for rapid fitting in the support rail; for bridging non-illuminated light run units, reflector mounting possible, sealed with all-round closed seal to the support rail to guarantee the protection type. Housing colour traffic white RAL 9016; . Light Control: netlife easy6; Regiolux Classification: netlife easy; Control signal: Switch; Number of control gear (max): 1100VA; Communication: Wired; Sensor technology: PIR - passive infrared; Installation height (min/max): 2m to 10m; Monitoring area: max. D=48m; Remote control: 84506027100; Optional remote control: 84506021200 +App; App name: B.E.G. One; System extension: easy19; Application: Corridors, Garages, Industry, Logistics centres, Secondary rooms, Office, Meeting rooms; Function: Motion detection, presence detection, Switch. Wired ready for connection via integrated connector. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	84181027204
EAN number	4020863321674
Commodity code	90328900
Certification mark	IP 54, Indoor, CE
Special properties	Advanced Services

ELECTRICAL ENGINEERING

Controller	easy06
Mains voltage	230V/50Hz

MECHANICS



Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1536mm x 102mm x 99mm
Weight (net)	1.2kg
Type of installation	Mounting rail system installation

Dimensions

L	1536 mm	Length
B	102 mm	Width
H	99 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/84181027204>



LC SYSTEM

CHARACTERISTICS

Regiolux Classification	netlife easy
Control signal	Switch
Number of control gear (max)	1100VA
Communication	Wired
Sensor technology	PIR - passive infrared
Installation height (min/max)	2m to 10m
Remote control	84506027100
Optional remote control	84506021200 +App
App name	B.E.G. One
System extension	easy19
Application	Corridors, Garages, Industry, Logistics centres, Secondary rooms, Office, Meeting rooms
Function	Motion detection, presence detection, Switch

MONITORING AREA

Mounting Height	3,5m	10m
Ø max. sitting[S]	9m	-
Ø max. radial[R]	-	16m
Ø max. tangential[T]	-	48m

