

universal-mounting rail - Universal mounting rail, flexible, current taps every 767.5 mm, for device mount module /750, /1500 and /2250

Torsion-resistant mounting rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal mounting rail suitable for light runs in all protection classes IP20 to IP64; Housing colour black RAL 9005; . Heat-resistant, feed-through wiring with individual conductors installed at the factory. Including 1 current tap for electrical connection of the device mounts, in module 750. With push connection at the end of the support rail for the fast electrical connection of further support rails. 2 pre-scored knock-outs at the top allow a direct feed via the support rail. Feed adaptor and optionally mounting rail with connection terminals required for medium or medium feed. The outfeed and central infeed can be done on site; information can be found in the installation instructions. Please order assembly accessories as well as rail end pieces and connectors separately. Halogen-free wiring is available on request. The mounting rail can be shortened if the building conditions so require.

## CHARACTERISTICS

|                    |  |
|--------------------|--|
| Order number       | 19277501104                                    |
| EAN number         | 4020863383641                                  |
| Commodity code     | 94059900                                       |
| Certification mark | IP 20/40/54/64, Protection class I, Indoor, CE |

## ELECTRICAL ENGINEERING

|        |                              |
|--------|------------------------------|
| Wiring | 5x2.5 / 6x1.5mm <sup>2</sup> |
|--------|------------------------------|

## MECHANICS

|                        |   |
|------------------------|---|
| Housing colour         | black RAL 9005  |
| Dimensions (LxWxH/DxH) | 767.5mm x 63mm x 46mm   |
| Weight (net)           | 0.95kg  |
| Type of installation   | Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure, Ceiling-mounted mounting rail installation, Ceiling-mounted mounting rail installation on T-system, Pendulum mounting rail assembly on chain, Pendulum mounting rail installation on steel cable |

## Dimensions

|   |          |        |
|---|----------|--------|
| L | 767.5 mm | Length |
| B | 63 mm    | Width  |
| H | 46 mm    | Height |

## DEEP-LINK

<https://www.regiolux.de/en/article/19277501104>

