

universal-mounting rail - Universal mounting rail, flexible, current taps every 767.5 mm, for device mount module /750, /1500 and /2250

Torsion-resistant support rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal support rail suitable for light runs of all protection classes IP20 to IP64; Housing colour black RAL 9005; . Heat-resistant, through-wiring with individual conductors installed in the factory. Including 6 current taps for electrical connection of the device mounts, in module 750. With push connection at the end of the mounting rail for the fast electrical connection of further mounting rails. 2 pre-scored knock-outs at the top allow a direct feed via the mounting rail. Feed adapter and optional mounting rail including outfeed required. Please order assembly accessories as well as rail end pieces and connectors separately.

## CHARACTERISTICS

Order number	19284506104
EAN number	4020863383795
Commodity code	94059900
Certification mark	IP 20/40/54/64, Protection class I, Indoor, CE

## ELECTRICAL ENGINEERING

Wiring	7x2.5mm <sup>2</sup>
--------	----------------------

## MECHANICS

Housing colour	black RAL 9005
Dimensions (LxWxH/DxH)	4605mm x 63mm x 46mm
Weight (net)	5.2kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure, Ceiling-mounted mounting rail installation, Ceiling-mounted mounting rail installation on T-system, Pendulum mounting rail assembly on chain, Pendulum mounting rail installation on steel cable

## Dimensions

L	4605 mm	Length
B	63 mm	Width
H	46 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19284506104>

