

universal-mounting rail - Universal mounting rail, flexible, current taps every 767.5 mm, for device mount module /750, /1500 and /2250

Torsion-resistant mounting rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal mounting rail suitable for light runs in all protection classes IP20 to IP64; Housing colour traffic white RAL 9016; . The inserted heat-resistant feed-through wiring contains colour-coded individual conductors and is equipped with a polarity reversal-proof plug-socket pair. The integrated lever plug-in connector enables a particularly fast and tool-less electrical connection of further mounting rails, it locks audibly and visibly during installation. Including 3 current taps for electrical connection of the gear trays, in module 750. For maximum flexibility, gear trays can be variably positioned 100% freely over the entire length of the light strip. 2 upper cut-out openings allow direct feeding.. Tool-less connection via separate feed adapter. The outfeed or centre infeed can be carried out either with pre-assembled outfeed rails or, as described in the installation instructions, without separate accessories. Please order assembly accessories as well as rail end pieces and connectors separately. Halogen-free wiring is available on request. The mounting rail can be shortened if the building conditions so require.

## CHARACTERISTICS

|                    |  |
|--------------------|--|
| Order number       | 19282253100                                    |
| EAN number         | 4020863423347                                  |
| Commodity code     | 94059900                                       |
| Certification mark | IP 20/40/54/64, Protection class I, Indoor, CE |

## ELECTRICAL ENGINEERING

|        |                      |
|--------|----------------------|
| Wiring | 7x2.5mm <sup>2</sup> |
|--------|----------------------|

## MECHANICS

|                        |   |
|------------------------|---|
| Housing colour         | traffic white RAL 9016  |
| Dimensions (LxWxH/DxH) | 2302.5mm x 63mm x 46mm  |
| Weight (net)           | 2.475kg   |
| Type of installation   | Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure, Ceiling-mounted mounting rail installation, Ceiling-mounted mounting rail installation on T-system, Pendulum mounting rail assembly on chain, Pendulum mounting rail installation on steel cable |

## Dimensions

|   |           |        |
|---|-----------|--------|
| L | 2302.5 mm | Length |
| B | 63 mm     | Width  |
| H | 46 mm     | Height |

## DEEP-LINK

<https://www.regiolum.de/en/article/19282253100>

