

IP 64 device mount - Individual.Lens.Optic - direct, extremely narrow distribution - visually continuous

Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Housing colour traffic white RAL 9016; Light distribution direct, extremely narrow distribution by means of Individual.Lens.Optic of PMMA plastic, With rack lighting, the single lens optics have a transparent seal, ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The inner rhythm of the 3-row single lens arrangement and the overriding device mount are perfectly in tune to guarantee a homogeneous appearance in the object. Suitable for VDU workstations,  $65^\circ < 3000 \text{ cd/m}^2$  omnidirectional glare reduction in accordance with current DIN-EN 12464-1 standard, UGR (4H/8H) 13.5. Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

Order number	19442006110
EAN number	4020863406852
Commodity code	94051190
Certification mark	IP 64, Protection class I, $\gamma$ $65^\circ < 3000 \text{ cd/m}^2$ , ENEC10 VDE, F, D, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (-20°C bis 25°C)
Ambient temperatur	ta -20°C to 25°C
Special properties	Ready for IoT
Warranty period	5 years

## ELECTRICAL ENGINEERING

Controller	Electronic driver DALI2 (1 pcs.)
System output	70W
Mains voltage	230V/50Hz
Energy efficiency class/light source	D

## LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI $\geq 80$ / 3000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	9442lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	135lm/W
Beam angle	30° (C0) / 30° (C90)
UGR lat./long.	13.5 / 12.1

## MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1531mm x 55mm x 37mm
Weight (net)	1.9kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure

## Dimensions

L	1531 mm	Length
B	55 mm	Width
H	37 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19442006110>



Reference	LED 10000lm 830
$\eta_{LB}$	100 %
$\Phi$ ↓/↑	99 % / 1 %
UGR lat./long.	13.5 / 12.1
VDU	$65^\circ < 3000 \text{ cd/m}^2$

