

IP 54 device mount - Matt diffuser - direct, open distribution

Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantee good corrosion protection; tool-free attachment with rotary catches for rapid fitting in the support rail. LED unit made of a natural anodised extruded aluminium profile with end faces made of plastic and an all-round closed seal to the support rail for a protection type up to IP54. Housing colour traffic white RAL 9016; Diffuser optics, Light distribution direct, open distribution by means of Matt diffuser of Polycarbonate, UGR (4H/8H) 29.2. Electrical connection by means of a fixed, 3-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. The device mount can be adjusted variably in steps with a multi-lumen driver (default setting: maximum lumen output). They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19102004030
EAN number	4020863417728
Commodity code	94051190
Certification mark	IP 54, Protection class I, F, D, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK06 (0°C bis 40°C)
Ambient temperatur	ta 0°C to 40°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic multi-lumen driver, 4-steps (1 pcs.)
System output	51W-29W
Mains voltage	230V/50Hz
Energy efficiency class/light source	B

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG0
Nominal luminous flux/switching steps	8100lm/51W, 7000lm/43W, 5900lm/36W, 4800lm/29W
LED service life	50000h L80/B10 (Tq 40°C)
Luminaire luminous efficiency	169lm/W-159lm/W
Beam angle	115° (C0) / 105° (C90)
UGR lat./long.	28.1 / 29.2 (51W)

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxDxH)	1531mm x 55mm x 43mm
Weight (net)	2kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure

Dimensions

L	1531 mm	Length
B	55 mm	Width
H	43 mm	Height

DEEP-LINK

<https://www.regiolum.de/en/article/19102004030>



Reference	LED 8100lm/51W 840
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	28.1 / 29.2

