

universal-mounting rail - Universal mounting rail, flexible, current taps every 767.5 mm, for device mount module /750, /1500 and /2250

5x2.5 / 6x1.5mm<sup>2</sup>

5.25kg

Torsion-resistant mounting rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal mounting rail suitable for light runs in all protection classes IP20 to IP64; Housing colour traffic white RAL 9016; . The inserted heat-resistant feed-through wiring contains colour-coded individual conductors and is equipped with a polarity reversal-proof plug-socket pair. The integrated lever plug-in connector enables a particularly fast and tool-less electrical connection of further mounting rails, it locks audibly and visibly during installation. Including 6 current taps for electrical connection of the gear trays, in module 750. For maximum flexibility, gear trays can be variably positioned 100% freely over the entire length of the light strip. 2 upper cut-out openings allow direct feeding. Tool-less connection via separate feed adapter. The outfeed or centre infeed can be carried out either with pre-assembled outfeed rails or, as described in the installation instructions, without separate accessories. Please order assembly accessories as well as rail end pieces and connectors separately. Halogen-free wiring is available on request. The mounting rail can be shortened if the building conditions so require.

## **CHARACTERISTICS**

Certification mark	IP 20/40/54/64, Protection class I, Indoor, CE	
Commodity code	94059900	
EAN number	4020863421015	
Order number	19274526100	

## **ELECTRICAL ENGINEERING**

MECHANICS	
Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	4605mm x 63mm x 46mm

# Type of installation

Weight (net)

Wiring

Mounting rail system installation,
Ceiling-mounted light structure, Pendant light
structure, Ceiling-mounted mounting rail
installation, Ceiling-mounted mounting rail
installation on T-system, Pendulum mounting
rail assembly on chain, Pendulum mounting
rail installation on steel cable

## **Dimensions**

L	4605 mm	Length
В	63 mm	Width
Н	46 mm	Height

#### **DEEP-LINK**

https://www.regiolux.de/en/article/19274526100

