SRT /1500/I-0750 5x2.5 / 6x1.5mm² • sw RAL 9005 • 19271502104

REGIOLUX

universal-mounting rail - Universal mounting rail, flexible, current taps every 767.5 mm, for device mount module /750, /1500 and /2250

Torsion-resistant mounting rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal mounting rail suitable for light runs in all protection classes IP20 to IP64; Housing colour black RAL 9005; . The inserted heat-resistant feed-through wiring contains colour-coded individual conductors and is equipped with a polarity reversal-proof plug-socket pair. The integrated lever plug-in connector enables a particularly fast and tool-less electrical connection of further mounting rails, it locks audibly and visibly during installation. Including 2 current taps for electrical connection of the gear trays, in module 750. For maximum flexibility, gear trays can be variably positioned 100% freely over the entire length of the light strip. 2 upper cut-out openings allow direct feeding.. Tool-less connection via separate feed adapter. The outfeed or centre infeed can be carried out either with pre-assembled outfeed rails or, as described in the installation instructions, without separate accessories. Please order assembly accessories as well as rail end pieces and connectors separately. Halogen-free wiring is available on request. The mounting rail can be shortened if the building conditions so require.

CHARACTERISTICS

Order number	19271502104
EAN number	4020863383528
Commodity code	94059900
Certification mark	IP 20/40/54/64, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Wiring	5x2.5 / 6x1.5mm²

MECHANICS

Housing colour	black RAL 9005
Dimensions (LxWxH/DxH)	1535mm x 63mm x 46mm
Weight (net)	1.9kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure, Ceiling-mounted mounting rail installation, Ceiling-mounted mounting rail installation on T-system, Pendulum mounting rail assembly on chain, Pendulum mounting rail installation on steel cable

Dimensions

L	1535 mm	Length
B	63 mm	Width
H	46 mm	Height

DEEP-LINK

https://www.regiolux.de/en/article/19271502104

max. 2500 mm max. 2500 mm max. 2500 mm

1500/III 1500/III

max. 20 kg max. 20 kg max. 20 kg