

universal-mounting rail - Universal mounting rail, flexible, current taps every 767.5 mm, for device mount module /750, /1500 and /2250

Torsion-resistant support rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal support rail suitable for light runs of all protection classes IP20 to IP64; Housing colour traffic white RAL 9016; . Heat-resistant, feed-through wiring with individual conductors installed at the factory. Including 1 current tap for electrical connection of the device mounts, in module 750. With push connection at the end of the support rail for the fast electrical connection of further support rails. 2 pre-scored knock-outs at the top allow a direct feed via the support rail. Feed adapter and optional mounting rail including outfeed required. Please order assembly accessories as well as rail end pieces and connectors separately.

CHARACTERISTICS

Order number	19287501100
EAN number	4020863383818
Commodity code	94059900
Certification mark	IP 20/40/54/64, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Wiring	7x2.5mm ²
--------	----------------------

MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	767.5mm x 63mm x 46mm
Weight (net)	0.875kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure, Ceiling-mounted mounting rail installation, Ceiling-mounted mounting rail installation on T-system, Pendulum mounting rail assembly on chain, Pendulum mounting rail installation on steel cable

Dimensions

L	767.5 mm	Length
B	63 mm	Width
H	46 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19287501100>

