

universal-mounting rail - Universal mounting rail, flexible, current taps every 767.5 mm, for device mount module /750, /1500 and /2250

Torsion-resistant mounting rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal mounting rail suitable for light runs in all protection classes IP20 to IP64; Housing colour black RAL 9005; . The inserted heat-resistant feed-through wiring contains colour-coded individual conductors and is equipped with a polarity reversal-proof plug-socket pair. The integrated lever plug-in connector enables a particularly fast and tool-less electrical connection of further mounting rails, it locks audibly and visibly during installation. Including 6 current taps for electrical connection of the gear trays, in module 750. For maximum flexibility, gear trays can be variably positioned 100% freely over the entire length of the light strip. 2 upper cut-out openings allow direct feeding. Tool-less connection via separate feed adapter. The outfeed or centre infeed can be carried out either with pre-assembled outfeed rails or, as described in the installation instructions, without separate accessories. Please order assembly accessories as well as rail end pieces and connectors separately. Halogen-free wiring is available on request. The mounting rail can be shortened if the building conditions so require.

CHARACTERISTICS

Order number	19284506104
EAN number	4020863383795
Commodity code	94059900
Certification mark	IP 20/40/54/64, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Wiring		/x2.5mm²

MECHANICS

MECHANICS	
Housing colour	black RAL 9005
Dimensions (LxWxH/DxH)	4605mm x 63mm x 46mm
Weight (net)	5.2kg
Type of installation	Mounting rail system installation,
	Ceiling-mounted light structure, Pendant light
	structure, Ceiling-mounted mounting rail
	installation, Ceiling-mounted mounting rail
	installation on T-system, Pendulum mounting
	rail assembly on chain, Pendulum mounting
	rail installation on steel cable

Dimensions

L	4605 mm	Length	
В	63 mm	Width	
Н	46 mm	Height	

DEEP-LINK

https://www.regiolux.de/en/article/19284506104

