

greenKit - Renovation solutions - Frosted diffuser - direct distribution - Renovation solution for CUBUS/Lura T8/1500

Refurbishment solution greenKit-Type2 for RSA, Cubus and Lura T8, module length/1500; easy, quick installation via a magnetic closure, enclosure made from painted sheet steel. Perfectly suited as a replacement for a conventional T8 lamp. Direct light distribution; the glare reduction is maintained when used in combination with the louvre and the iced diffuser made from PMMA. The uniform light source ensures homogeneous illumination; the limitation of glare effects of the existing luminaire is maintained. Electrical connection via 3-pole through-wiring terminal in plug-in contact technology. Protective earth contact is established via a screw connection to the luminaire enclosure; high efficiency due to non SELV. Technical lighting data on request. Suitable for the refurbishment of T8 luminaires. The fitter has legal certainty through EMC testing, the CE mark and a 5 year warranty, as well as a 100% warranty from the manufacturer.

CHARACTERISTICS

| Order number | 79400054100 |
|-------------------------------|---|
| EAN number | 4020863481101 |
| Commodity code | 94051190 |
| Certification mark | IP 20, Protection class I, F, Indoor, CE |
| Impact resistance (IK rating) | IK03 |
| Ambient temperatur | ta 25°C |
| Warranty period | 5 years |
| State funding programs | BEG - Federal funding for efficient buildings (valid only for Germany) |

ELECTRICAL ENGINEERING

| Controller | Electronic driver (1 pcs.) |
|--------------------------------------|----------------------------|
| System output | 30W |
| Mains voltage | 230V/50Hz |
| Energy efficiency class/light source | С |

LIGHTING TECHNOLOGY


| Placement | LED, Colour rendering/Light colour CRI ≥ 80 / 3000K |
|------------------------------------|--|
| Colour tolerance (MacAdam) | 3SDCM |
| Photobiological safety (Luminaire) | RG1 |
| Nominal luminous flux | 4703lm |
| LED service life | 70000h L80/B10 (Tq 25°C/für Anbauleuchte) |
| Luminaire luminous efficiency | 156lm/W |

MECHANICS

| Housing colour | traffic white RAL 9016 |
|------------------------|------------------------|
| Dimensions (LxWxH/DxH) | 1467mm x 97mm x 32mm |
| Weight (net) | 0.94kg |
| Type of installation | Magnetic fastening |

Dimensions





General warranty conditions: www.regiolux.de/en/Service/Warranty Regiolux GmbH - www.regiolux.de -Subject to changes - 22.07.2024