

Mounting rail - Universal mounting rail, current taps every 1535 mm, for device mount module /1500

Torsion-resistant support rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal support rail suitable for light runs of all protection classes IP20 to IP64; Housing colour traffic white RAL 9016; . Ribbon cabling installed and wired to quick-fit socket unit in the factory. Please order separately connection and assembly accessories as well as rail end pieces and connectors.

## CHARACTERISTICS

|                    |  |
|--------------------|--|
| Order number       | 18253580100                                    |
| EAN number         | 4020863035809                                  |
| Commodity code     | 94059900                                       |
| Certification mark | IP 20/40/54/64, Protection class I, Indoor, CE |

## ELECTRICAL ENGINEERING

|        |                      |
|--------|----------------------|
| Wiring | 5x1.5mm <sup>2</sup> |
|--------|----------------------|

## MECHANICS

|                        |                                   |
|------------------------|-----------------------------------|
| Housing colour         | traffic white RAL 9016            |
| Dimensions (LxWxH/DxH) | 4605mm x 63mm x 46mm              |
| Weight (net)           | 4.6kg                             |
| Type of installation   | Mounting rail system installation |

## Dimensions

|   |         |        |
|---|---------|--------|
| L | 4605 mm | Length |
| B | 63 mm   | Width  |
| H | 46 mm   | Height |

## DEEP-LINK

<https://www.regiolux.de/en/article/18253580100>

